

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Delphion

RESEARCH

INTEGRATED IAM

SERVICES

INSIDE DELPHION



My Account | Products | News | Events

Search: Quick/Number Boolean Advanced

The Delphion Integrated View


Buy Now:  PDF | [More choices...](#)Tools: Add to Work File: [Create new Work File](#) View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent...](#) [Email this to a friend](#)

 Title: **JP5283060A2: NEGATIVE ELECTRODE FOR LITHIUM SECONDARY BATTERY, MANUFACTURE OF THE NEGATIVE ELECTRODE AND LITHIUM SECONDARY BATTERY USING SAME NEGATIVE ELECTRODE**


 Country: **JP Japan**
 Kind: **A**


 Inventor: **MABUCHI AKIHIRO;
NAKAGAWA YOSHITERU;
YAMASHITA MITSUO;**


 Assignee: **OSAKA GAS CO LTD**
[News, Profiles, Stocks and More about this company](#)

 Published / Filed: **Oct. 29, 1993 / March 30, 1992**

 Application Number: **JP1992000073846**


 IPC Code: **H01M 4/02; H01M 4/04; H01M 4/58; H01M 10/40;**


 Priority Number: **March 30, 1992 JP1992000073846**


 Abstract: **Purpose:** To substantially improve discharge capacity by using a mesophase small ball having surface baked after treatment with quinoline, as a lithium carrier.

Constitution: A mesophase small ball (MCMB) is subjected to quinoline treatment and then to baking treatment. The quinoline treatment in this case is such that MCMB is kept in contact with quinoline in a static or agitating condition, generally for 0.5 to 3 hours at a temperature within the range of 10 to 80°C, or preferably for 1 to 2 hours at a temperature within the range of 20 to 30°C. As a result of the treatment in that condition, the surface of MCMB is impregnated with quinoline and treated accordingly. After the quinoline treatment, MCMB is preferably dried and then subjected to baking treatment. This baking treatment is conducted in inert gas atmosphere such as nitrogen and argon at a temperature within the range of 650 to 1400°C. MCMB after baked is kneaded with a suitable binder, and molded under pressure to form an electrode body, thereby providing a negative electrode for a lithium secondary battery.

COPYRIGHT: (C)1993,JPO&Japio

 Family: **None**

 Other Abstract Info: **CHEMABS 120(06)058600H CAN120(06)058600H DERABS C93-380581
DERC93-380581**



[View
Image](#)

1 page



[this for the Gallery...](#)



[Nominate](#)

